

Advanced

ACPI Configuration

Suspend Mode	[Enabled]
ACPI HPET Table	[Enabled]
PS/2 Keyboard Power On	[Disabled]
PCI Devices Power On	[Disabled]
RTC Alarm Power On	[By OS]
Ring-In Power On	[Disabled]

Select the highest ACPI sleep state the system will enter when the SUSPEND button is pressed.

↔: Select Screen
↑↓: Select Item
Enter: Select
+/-: Change Option
F1: General Help
F7: Discard Changes
F9: Load UEFI Defaults
F10: Save and Exit
ESC: Exit

Advanced

WHEA Support

[Enabled]

Enable or disable Windows
Hardware Error Architecture.

↔: Select Screen
↑↓: Select Item
Enter: Select
+/-: Change Option
F1: General Help
F7: Discard Changes
F9: Load UEFI Defaults
F10: Save and Exit
ESC: Exit

Advanced

CPU Configuration

▶ CPU_BSP1 Information

▶ CPU_AP1 Information

CPU Speed 2100 MHz
64-bit Supported

Intel Hyper Threading Technology [Enabled]
Active Processor Cores [All]
Limit CPUID Maximum [Disabled]
No-Execute Memory Protection [Enabled]
Hardware Prefetcher [Enabled]
Adjacent Cache Line Prefetch [Enabled]
DCU Streamer Prefetcher [Enabled]
DCU IP Prefetcher [Enabled]
Intel Virtualization Technology [Enabled]
PPIN Support [Disabled]

▶ CPU Power Management Configuration

Socket specific CPU Information

↔: Select Screen
↑↓: Select Item
Enter: Select
+/-: Change Option
F1: General Help
F7: Discard Changes
F9: Load UEFI Defaults
F10: Save and Exit
ESC: Exit

Advanced

CPU Power Management Configuration

Power Technology	[Energy Efficient]
Energy Performance	[Performance]
Factory long duration power limit	80 Watts
Long duration power limit	0
Factory long duration maintained	10 s
Long duration maintained	0
Recommended short duration power 1	1.2 * Long Duration
Short duration power limit	0

Enable the power management features.

↔: Select Screen
↑↓: Select Item
Enter: Select
+/-: Change Option
F1: General Help
F7: Discard Changes
F9: Load UEFI Defaults
F10: Save and Exit
ESC: Exit

Advanced

Intel(R) VT-d	[Disabled]
Intel(R) I/OAT	[Enabled]
Primary Graphics Adapter	[PCI Express]
OnBoard VGA	[Disabled]

PCIE 1 Link Speed	[GEN3]
PCIE 3 Link Width	[x16]
PCIE 3 Link Speed	[GEN3]
PCIE 4 & PCIE 5 Link Width	[Auto]
PCIE 4 & PCIE 5 Link Speed	[GEN3]
PCIE 6 Link Width	[x16]
PCIE 6 Link Speed	[GEN3]
PCIE 7 Link Width	[x16]
PCIE 7 Link Speed	[GEN3]

Enable/Disable Intel(R)
Virtualization Technology for
Directed I/O.

↔: Select Screen
↑↓: Select Item
Enter: Select
+/-: Change Option
F1: General Help
F7: Discard Changes
F9: Load UEFI Defaults
F10: Save and Exit
ESC: Exit

Advanced

Current QPI Link Speed	Fast
Current QPI Link Freq	7.2 GT/s
Isoc	[Enabled]
QPI Link Speed Mode	[Fast]
QPI Link Frequency Select	[Auto]
Snoop Mode	[Auto]

Enbale /Disable Isoc

↔: Select Screen
↑↓: Select Item
Enter: Select
+/-: Change Option
F1: General Help
F7: Discard Changes
F9: Load UEFI Defaults
F10: Save and Exit
ESC: Exit

Advanced

Memory Configuration

Total Memory	65536 MB (DDR3)
Current Memory Mode	Independent
Current Memory Speed	1333 MHz
Mirroring	Supported
Sparing	Not Possible
Memory Mode	[Independent]
ECC Support	[Auto]
DRAM RAPL BWLIMIT	[1]
Perfmon and DFX devices	[HIDE]
DRAM RAPL MODE	[DRAM RAPL MODE1]
Numa	[Enabled]
MPST Support	[Disabled]
DRAM Frequency	[Auto]
Channel Interleaving	[Auto]
Rank Interleaving	[Auto]
Patrol Scrub	[Enabled]
Demand Scrub	[Disabled]
Data Scrambling	[Disabled]
Thermal Throttling	[CLTT]

Select the mode for memory initialization.

↔: Select Screen
↑↓: Select Item
Enter: Select
+/-: Change Option
F1: General Help
F7: Discard Changes
F9: Load UEFI Defaults
F10: Save and Exit
ESC: Exit

► DIMM Information

Advanced

Restore on AC/Power Loss [Power Off]

Onboard LAN 1 [Enabled]

Onboard LAN 2 [Enabled]

Onboard Debug Port LED [Off]

Specify what state to go to when power is re-applied after a power failure (G3 state).

←→: Select Screen

↑↓: Select Item

Enter: Select

+/-: Change Option

F1: General Help

F7: Discard Changes

F9: Load UEFI Defaults

F10: Save and Exit

ESC: Exit

Advanced

USB 2.0 Controller	[Enabled]
Legacy USB Support	[Enabled]

To enable or disable USB 2.0 Controller.

↔: Select Screen
↑↓: Select Item
Enter: Select
+/-: Change Option
F1: General Help
F7: Discard Changes
F9: Load UEFI Defaults
F10: Save and Exit
ESC: Exit

Advanced

Spread Spectrum

[Disabled]

Config the feature of spread spectrum.

←→: Select Screen

↑↓: Select Item

Enter: Select

+/-: Change Option

F1: General Help

F7: Discard Changes

F9: Load UEFI Defaults

F10: Save and Exit

ESC: Exit

Advanced

SATA Mode Selection	[AHCI Mode]
SATA Aggressive Link Power Mgmt	[Disabled]
Hard Disk S.M.A.R.T	[Enabled]
Marvell 9230 SATA3_M0~M3 Operation	[Disabled]
SCU devices	[Disabled]

▶ SATAIII_0 : HL-DT-ST BD-RE WH16NS40
▶ SATAIII_1 : Samsung SSD 850 EVO 500GB
▶ SATAII_2 : Not Detected
▶ SATAII_3 : Not Detected
▶ SATAII_4 : Not Detected
▶ SATAII_5 : Not Detected
▶ SATAIII_M0_M1_M2_M3

(1) IDE Mode. (2) AHCI Mode.
(3) RAID Mode.
Press <Ctrl - I> to enter RAID
ROM during UEFI POST process.

↔: Select Screen
↑↓: Select Item
Enter: Select
+/-: Change Option
F1: General Help
F7: Discard Changes
F9: Load UEFI Defaults
F10: Save and Exit
ESC: Exit

Advanced

SATAIII_0 Hot Plug [Disabled]
Staggered Spin-up [Disabled]

Model Number : HL-DT-ST BD-RE WH
Serial Number : K9PI1T85915

Ultra DMA : 6
S.M.A.R.T. : Not Supported

SATA Ports Hot Plug Support

↔: Select Screen
↑↓: Select Item
Enter: Select
+/-: Change Option
F1: General Help
F7: Discard Changes
F9: Load UEFI Defaults
F10: Save and Exit
ESC: Exit

Advanced

Serial Port 1 Configuration

Serial Port

[Disabled]

Enable or Disable Serial Port
(COM)

←→: Select Screen

↑↓: Select Item

Enter: Select

+/-: Change Option

F1: General Help

F7: Discard Changes

F9: Load UEFI Defaults

F10: Save and Exit

ESC: Exit

Advanced

Serial Port 2 Configuration

Serial Port

[Disabled]

Enable or Disable Serial Port
(COM)

←→: Select Screen

↑↓: Select Item

Enter: Select

+/-: Change Option

F1: General Help

F7: Discard Changes

F9: Load UEFI Defaults

F10: Save and Exit

ESC: Exit

Advanced

Voltage Control

DRAM 1 Voltage	1.500V	[Auto]
DRAM 2 Voltage	1.500V	[Auto]
PLL 1 Voltage	1.810V	[Auto]
PLL 2 Voltage	1.810V	[Auto]
VTT 1 Voltage	1.050V	[Auto]
VTT 2 Voltage	1.050V	[Auto]
PCH Voltage	1.100V	[Auto]

DRAM Voltage Configuration.

↔: Select Screen
↑↓: Select Item
Enter: Select
+/-: Change Option
F1: General Help
F7: Discard Changes
F9: Load UEFI Defaults
F10: Save and Exit
ESC: Exit